

METHOD FOR MOUNTING DISPLAY PANEL USED IN INFORMATION PROCESSING
APPARATUS AND DISPLAY PANEL HOUSING THEREFOR

BACKGROUND OF THE INVENTION

5

Field of the Invention

the present invention relates to a method for mounting¹
display panel used in information processing apparatus and
10 display panel housing therefor and a display panel housing of the
same, and more particularly to a method for mounting a display
panel selected from various kinds of display panels in a
predetermined common display panel housing installed in an
open-and-close manner or detachably on a main body of an
15 information processing apparatus such as a notebook personal
computer or ~~a~~^{the} like, and the display panel housing.

The present application claims priority ^{to} Japanese Patent
Application No.2000-125460 filed on April 26,2000, which is
hereby incorporated by reference.

20

Description of the Related Art

Recently, in general, a liquid crystal display portion of
an open-and-close type is installed on a main body of an
25 information processing apparatus such as a notebook personal
computer or ~~a~~^{the} like which has been rapidly popularized.

The liquid crystal display portion is manufactured as an
integral structure body of a display panel housing, that is a
display cover plate of a visual field is used or functions as a

JOG
10/14/02

cover lid on the display panel installed in an ~~an~~ panel-mounting case.

However, there are many occasions in which the liquid crystal display portion changes in a display picture size of the display panel, a display resolution, or a thickness and a shape of the display panel.

Therefore, it has been necessary, ^{on} ~~in~~ such occasions, to change the whole structure of the display panel housing. Practically, the expensive display panel housing has been unavoidably changed and discarded.

As described above, a display picture size of the display panel, display resolution, or a thickness and a shape of the display portion of many conventional information display portions installed on the main body of the information processing apparatus such as the notebook personal computer or a ^{the} like so as to open and close, or be detachable have been changed for long period. ^{here} Ordinarily, it is a general way to exchange a new display panel housing and the information display portion included in the housing with an old one.

In the foregoing, it is preferable, economically, and ~~effective~~ ^{effective} [extraordinarily] if the display panels of many kinds can be installed in the identical display panel housing of the same kind decreasing a number of parts to be discarded without changing the whole structure of the panel-mounting cases.

In addition, if it is possible to exchange an old display panel with a new display panel of highest technology at the time and mount the new one without changing the design of the panel-mounting case in order, it will follow to extend a life of the information processing apparatus.

JCG
10/14/02

SUMMARY OF THE INVENTION

In view of the above, it is an object of the present invention
5 to provide a display panel mounting method capable of mounting,
with a low cost and with ease and universally, a display panel
selected from various kinds of display panels in a predetermined
common display panel housing installed in an open-and-close
manner or detachably on a main body of an information processing
10 apparatus such as a notebook personal computer or a like, and the
display panel housing ①

According to a first aspect of the present invention, there
is provided a method for mounting a display panel selected from
various kinds of display panels in a predetermined common display
15 panel housing installed in an open-and-close manner or detachably
on a main body of an information processing apparatus, wherein
the display panel housing has a predetermined panel-mounting case
for inserting the display panel therein and a predetermined
panel-edge cover for covering edge portions of the display panel,
20 the method including:

a step of inserting the display panel in the predetermined
panel-mounting case through at least one first spacer, whereby
the at least one first spacer is placed between a back face of
the display panel and an inner main-face of the panel-mounting
25 case;

a step of fixedly holding the display panel in the
panel-mounting case with at least two holding members, disposed
at different positions ^{to 2} each other; and

a step of covering edge portions of the display panel in

JDG
10/14/02

the panel-mounting case with the predetermined edge-cover;

whereby the display panel is mounted in the predetermined common display panel housing.

In the foregoing first aspect, a preferable mode is one that
5 wherein further includes:

a step of positioning and fixing the display panel along its up-and-down direction panel with at least one second spacer, wherefore the at least one second spacer is provided between a lower inner side face of the panel-mounting case and a lower outer
10 side face of the display panel.

Also, a preferable mode is one wherein the various kinds of display panels are different from each other in any one of shape, thickness, picture quality, and display screen size.

Also, a preferable mode is one wherein the at least two
15 holding members, the at least one first spacer and the at least one second spacer are used in combination in accordance with each of the various kinds of display panels.

Also, a preferable mode is one wherein the holding members are fixed to the panel-mounting case by screw-fixing or fitting.

20 According to a second aspect of the present invention, there is provided a display panel housing installed in an open-and-close manner or detachably on a main body of an information processing apparatus, mounting a display panel selected from various kinds of display panels, the display panel housing
25 comprising:

a predetermined panel-mounting case for inserting the display panel therein;

a predetermined panel-edge cover for covering edge portions of the display panel;

105200-3000000

at least one first spacer sandwiched between a back face of the display panel and an inner main-face of the panel-mounting case, such that the display panel is placed in the predetermined panel-mounting case through at least one first spacer;

5 at least two holding members disposed at different positions from each other, with which the display panel is fixedly held in the panel-mounting case;

wherein edge portions of the display panel are covered in the panel-mounting case with the predetermined panel-edge cover;
10 and

whereby the display panel is mounted in the predetermined common display panel housing.

In the foregoing second aspect, a preferable mode is one that wherein further including:

15 at least one second spacer for positioning and fixing the display panel along its up-and-down direction panel, wherefore the at least one second spacer is provided between a lower inner side face of the panel-mounting case and a lower outer side face of the display panel.

20 Also, a preferable mode is one wherein the various kinds of display panels are different from each other in any one of shape, thickness, picture quality, and display screen size.

Also, a preferable mode is one wherein the at least two holding members, the at least one first spacer and the at least
25 one second spacer are used in combination in accordance with each of the various kinds of display panels.

With the above configurations, it is possible to employ and mount various display panels different in one or all of shape, thickness, size, and display resolution without changing the

display panel housing. This can be accomplished by means of using a common panel-mounting case and a common display cover of the display panel housing and some spacers of a shape of simple manufacture.

5. Concerning a change of the display panel size, the display cover can be changed so as to be suitable to the particular display panel size by means of change of necessary parts of a minimum number.

Also, it is possible to decrease extraordinary deformation stresses created in a structure of the display panel even though the panel-mounting case and the display cover bend or deform because that the display panel is not directly screw-fixed or bond-fixed.

- 15 In case that the display panel must be changed to another one, it is not needed to change as the conventional way does the display panel housing, thus enabling to decrease a volume of parts to be discarded or wasted.

BRIEF DESCRIPTION OF THE DRAWINGS

20

The above and other objects, advantages, and features of the present invention will be more apparent from the following description taken in conjunction with the accompanying drawings in which:

- 25 Fig. 1 is a perspective view for showing an information processing apparatus (notebook personal computer) with a display cover of a display panel housing removed, according to an embodiment of the present invention, and

Fig. 2 is an exploded perspective view of the display panel

JDG
10/14/02

according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PRERERRED EMBODIMET

spelling

5 *the b*
Best mode of carrying out the present invention will be described in further detail using a preferable embodiment with reference to the accompanying drawings.

EMBODIMENT

10

Figure 1 and Figure 2 show a notebook personal computer as an information processing apparatus, according to an embodiment of the present invention.

15 The display panel housing according to the embodiment, as shown in Fig. 1, is installed in an open-and-close on a main body of a notebook personal computer.

In a display panel housing, as shown in the same figure, a particular display panel 2 is mounted in a predetermined common panel-mounting case 1. For example, as shown in Fig. 1, the display
20 panel 2 is fixed in the panel-mounting case 1 by screws and holding members 3 placed at four corners of the display panel 2.

As shown in Fig. 2, first spacers 4 placed near four corners of the panel-mounting case 1 and on an inner main-face of the panel-mounting case 1, and second spacers 5 placed between an
25 inner main-face of the panel-mounting case 1 and a side face of the display panel 2, which side faces are positioned at their lower positions when the display panel 2 is open as shown in Fig. 1. Accordingly, the first spacers 4 support a rear face of the display panel 2 and the second spacers 5 prevent the display panel 2 from

JOS
10/14/02

shifting along an up-and-down direction while the display panel 2 is erected.

Furthermore, in particular, the second spacers 5 are placed between the display panel 2 and tilt hinges 7 when the display panel 2 is open, so that the second spacers 5 ~~prevent~~ ^{effectively} the display panel 2 from shifting due to outside shocks.

After the display panel ^{panel 12 15} moved in the panel-mounting case 1 in a manner as described above, the holding members 3 are placed at four corners of the display panel 2 so as to fit on these corners of the display panel 2, and then these holding members 3 are fixed in place by a number of screws. Then a display cover 6 is applied to and covers the panel-mounting case 1 so as to be detachable by means of suitable means.

The second spacers 5 are placed between a lower inner side face of the panel-mounting case 1 and a lower outer side face of the display panel 2 when the open type display panel housing is erected. The second spacers 5 function as a set of members fixing and placing the display panel 2 preventing the display panel 2 from sliding along ^{on} up-and-down direction while the display panel housing is open.

Consequently, even if the display panels 2 are different from each other or of various kinds as described above, and the panel-mounting case 1 and the display cover 6, respectively of the display panel housing are of a common predetermined type, the display panels 2 can be mounted as one integral structure in the panel-mounting case 1 simply, and it is not necessary to change the panel-mounting case 1 and the display cover 6 of high cost by using various combinations of the first spacers 4, the second spacers 5 and the holding members 3.

JDB
10/14/02

It is apparent that the present invention is not limited to the above embodiment but may be changed and modified without departing from the scope and spirit of the invention. For example, it is also possible to employ any suitable means instead of the holding members 3, for example, a fitting-type (not shown), other than the screw-type, in order to fix the display panel 2 in the panel-mounting case 1.

Also, a display panel housing may be installed detachably in instead of an open-and-close manner on a main body of an information processing apparatus.

It is also possible to use other different means for holding and fixing the display panel 2, other than the holding members 3, pressing both side faces or upper and bottom faces of the open display panel 2. Fixing the display panel 2 through its two corners on a diagonal line of the panel 2 is ^a suitable way.

As described above, with the above embodiment of the present invention, it is possible to employ and mount various display panels different in one or all of shape, thickness, size, and display resolution without changing the display panel housing by means of using a common panel-mounting case and a common display cover of the display panel housing and some spacers of a shape of simple manufacturing.

Concerning a change of the display panel size, the display cover can be changed so as to be suitable to the particular display panel size by means of a change of necessary parts of minimum number.

Also, it is possible to decrease extraordinary deformation stresses created in a structure of the display panel even though the panel-mounting case and the display cover bend or deform

JDG
10/14/02

that

that -

JOG
10/14/02

姓名	性别	年龄	籍贯	职业	住址	电话	备注
王德胜	男	45	山东	教师	济南市	1234	
李秀英	女	38	河北	医生	石家庄市	5678	
张国强	男	52	河南	工人	郑州市	9012	
刘小红	女	28	湖北	学生	武汉市	3456	
陈为民	男	60	四川	农民	成都市	7890	
赵子龙	男	35	广东	商人	广州市	2345	
周大伟	男	48	浙江	工程师	杭州市	6789	
吴小芳	女	32	江苏	护士	南京市	0123	
孙建国	男	55	安徽	干部	合肥市	4567	
郑晓琳	女	25	江西	学生	南昌市	8901	
冯志强	男	40	福建	工人	福州市	2109	
马丽娟	女	30	广西	教师	南宁市	5432	
黄永年	男	58	湖南	农民	长沙市	9876	
徐文杰	男	33	贵州	商人	贵阳市	3210	
宋小华	女	27	云南	学生	昆明市	6543	
林大刚	男	42	陕西	工人	西安市	0987	
周美玲	女	36	甘肃	教师	兰州市	4321	
孙国强	男	50	青海	干部	西宁市	7654	
郑晓琳	女	29	宁夏	学生	银川市	1098	
冯志强	男	44	新疆	工人	乌鲁木齐市	5321	
马丽娟	女	31	内蒙古	教师	呼和浩特市	9654	
黄永年	男	56	吉林	农民	长春市	3987	
徐文杰	男	37	辽宁	商人	沈阳市	7210	
宋小华	女	26	黑龙江	学生	哈尔滨市	0543	
林大刚	男	41	河北	工人	石家庄市	4876	
周美玲	女	35	山东	教师	济南市	8109	
孙国强	男	49	河南	干部	郑州市	2432	
郑晓琳	女	28	湖北	学生	武汉市	6765	
冯志强	男	43	湖南	工人	长沙市	0098	
马丽娟	女	32	广东	教师	广州市	4321	
黄永年	男	57	广西	农民	南宁市	8654	
徐文杰	男	38	贵州	商人	贵阳市	2987	
宋小华	女	27	云南	学生	昆明市	7310	
林大刚	男	42	陕西	工人	西安市	1643	
周美玲	女	36	甘肃	教师	兰州市	5976	
孙国强	男	50	青海	干部	西宁市	9309	
郑晓琳	女	29	宁夏	学生	银川市	3632	
冯志强	男	44	新疆	工人	乌鲁木齐市	7965	
马丽娟	女	31	内蒙古	教师	呼和浩特市	1298	
黄永年	男	56	吉林	农民	长春市	5631	
徐文杰	男	37	辽宁	商人	沈阳市	9964	
宋小华	女	26	黑龙江	学生	哈尔滨市	4297	
林大刚	男	41	河北	工人	石家庄市	8630	
周美玲	女	35	山东	教师	济南市	2963	
孙国强	男	49	河南	干部	郑州市	7296	
郑晓琳	女	28	湖北	学生	武汉市	1629	
冯志强	男	43	湖南	工人	长沙市	5962	
马丽娟	女	32	广东	教师	广州市	9395	
黄永年	男	57	广西	农民	南宁市	3728	
徐文杰	男	38	贵州	商人	贵阳市	8061	
宋小华	女	27	云南	学生	昆明市	2394	
林大刚	男	42	陕西	工人	西安市	6727	
周美玲	女	36	甘肃	教师	兰州市	1060	
孙国强	男	50	青海	干部	西宁市	5393	
郑晓琳	女	29	宁夏	学生	银川市	9726	
冯志强	男	44	新疆	工人	乌鲁木齐市	4059	
马丽娟	女	31	内蒙古	教师	呼和浩特市	8392	
黄永年	男	56	吉林	农民	长春市	2725	
徐文杰	男	37	辽宁	商人	沈阳市	7058	
宋小华	女	26	黑龙江	学生	哈尔滨市	1391	
林大刚							